

# General Standard Battery Series

## Lead Acid Battery

- Capacity range: **0.3AH to 260AH**
- Rated voltage: **4V, 6V, 12V, 24V**
- Designed **floating charge life**: 5-10 years
- Meet IEC, JIS, BS, VDS and GB/T testing standards
- Pass UL, CE, ISO9001, ISO14001 and ISO45001 certifications
- Adopt 1# electrolytic lead with a purity of up to 99.994%
- Adopt special patented alloy formula, the grid has stronger corrosion resistance
- Adopt high temperature and high humidity curing process, the life, capacity and batch consistency are guaranteed
- The ear hanging process design has high consistency of plate curing and drying
- Adopt hidden safety valve design to effectively avoid safety valve blockage



No.	Model	Rated Voltage (V)	Rated Capacity (AH)	Terminal	Battery Dimension (mm)				Weight (Kg) ±3%
					Length	Width	Height	Total Height	
1	GS4-4	4	4	F1	48	48	101	106	0.45
2	GS4-6	4	6	F1	70	47	100	106	0.68
3	GS6-1.3	6	1.3	F1	97	24	51	55	0.26
4	GS6-2.8	6	2.8	F1	66	33	97	102	0.56
5	GS6-3.2	6	3.2	F1	125	33	60	64	0.63
6	GS6-3.3	6	3.3	F1	134	34	60	64	0.64
7	GS6-4	6	4	F1	70	47	100	106	0.71
8	GS6-4.5	6	4.5	F1	70	47	100	106	0.72
9	GS6-5	6	5	F1	70	47	100	106	0.75
10	GS6-7	6	7	F1	151	35	94	100	1.05
11	GS6-9	6	9	F1	151	35	94	100	1.25
12	GS6-10	6	10	F1	151	50	94	100	1.65
13	GS6-12	6	12	F1	151	50	94	100	1.75
14	GS12-0.8	12	0.8	W	96	26	62	62	0.32
15	GS12-1.3	12	1.3	F1	97	43	52	57	0.55
16	GS12-2.2	12	2.2	F1	70	48	99	102	0.75
17	GS12-2.3	12	2.3	F1	179	35	61	66	0.9
18	GS12-2.9	12	2.9	F1	80	56	99	103	1.05
19	GS12-3.3	12	3.3	F1	134	67	61	66	1.3
20	GS12-4	12	4	F1/F2	90	70	101	105	1.38
21	GS12-4.5	12	4.5	F1/F2	90	70	101	105	1.43
22	GS12-5	12	5	F1/F2	90	70	101	105	1.5
23	GS12-6	12	6	F1/F2	151	51	94	98	1.82
24	GS12-6.5	12	6.5	F1/F2	151	65	94	98	1.95
25	GS12-7	12	7	F1/F2	151	65	94	98	2.05
26	GS12-7.2	12	7.2	F1/F2	151	65	94	98	2.1
27	GS12-7.5	12	7.5	F1/F2	151	65	94	98	2.2
28	GS12-8	12	8	F1/F2	151	65	94	98	2.35
29	GS12-9	12	9	F1/F2	151	65	94	98	2.5
30	GS12-10	12	10	F1/F2	151	98	94	98	3.15
31	GS12-12	12	12	F1/F2	151	98	94	98	3.4
32	GS12-13	12	13	F1/F2	151	98	94	98	3.6
33	GS12-15	12	15	L1/M5	181	77	167	167	4.5
34	GS12-17	12	17	L1/M5	181	77	167	167	5
35	GS12-18	12	18	L1/M5	181	77	167	167	5.3
36	GS12-20	12	20	L1/M5	181	77	167	167	5.5
37	GS12-22	12	22	L1/M5	181	77	167	167	6.1
38	GS12-24	12	24	L2/M5	175	166	125	125	7.2
39	GS12-26	12	26	L2/M5	175	166	125	125	7.5
40	GS12-28	12	28	L2/M5	175	166	125	125	7.8
41	GS12-28L	12	28	L2/M5	165	126	174	174	8
42	GS12-33	12	33	L3/M5	196	133	161	170	10.5
43	GS12-40	12	40	L4/M5	196	165	170	170	13
44	GS12-45	12	45	L4/M5	196	165	170	170	14
45	GS12-50	12	50	M5	196	165	170	170	16
46	GS12-55	12	55	M5	230	137	210	215	16.5
47	GS12-60	12	60	M5	230	137	210	215	17.5
48	GS12-65	12	65	M5	350	167	174	174	20.5
49	GS12-70	12	70	M5	260	167	213	216	20.6
50	GS12-75	12	75	M5	260	167	213	216	21.5
51	GS12-80	12	80	M6	260	167	213	216	22.5
52	GS12-85	12	85	M6	260	167	213	216	25.7
53	GS12-90	12	90	M6	305	167	210	213	27
54	GS12-100	12	100	M8	305	167	210	213	28.2
55	GS12-100A	12	100	M8	330	173	217	220	29.5
56	GS12-120	12	120	M8	406	173	236	236	33.5
57	GS12-150	12	150	M8	486	171	243	243	41.5
58	GS12-200	12	200	M8	523	240	219	223	57
59	GS12-250	12	250	M8	520	269	220	224	69
60	GS12-260	12	260	M8	520	269	220	224	72