

Deep Cycle Battery Series

Lead Acid Battery

· Capacity range: 26AH to 3000AH

Rated voltage: 2V, 6V, 12V

Designed floating charge life: 10 years

· Non-spillable

• Sealed and maintenance-free operation

· High quality and high reliability

• Exceptional deep discharge recovery

• Low self-discharge

· Long service life

Solid copper terminals

Tank-formed plates

Computer-aided design and manufacturing

• Pass UL, CE, ISO9001, ISO14001 and ISO45001 certifications



	:								
No.	Model	Rated Voltage (V)	Rated Capacity (AH)	Terminal	Battery Dimension (mm)				Weight (Kg)
					Length	Width	Height	Total Height	±3%
1	DC6-150	6	150	M8	260	180	245	250	23.5
2	DC6-190	6	190	M8	243	187	253	276	28.5
3	DC6-200	6	200	F15/M8	321	176	226	246	30.5
4	DC6-220	6	220	F15/M8	243	187	253	276	32
5	DC8-180	8	180	M8	260	182	295	298	36.5
6	DC12-20	12	20	L1/M5	181	77	167	167	5.6
7	DC12-24	12	24	L1/M5	175	166	125	125	7.8
8	DC12-28	12	28	L1/M5	175	166	125	125	8.6
9	DC12-33	12	33	L3/M5	196	133	161	170	9.5
10	DC12-40	12	40	L4/M5	196	165	170	170	12.5
11	DC12-55	12	55	M5	230	137	210	215	16.5
12	DC12-60	12	60	M5	260	167	213	216	18.5
13	DC12-65	12	65	M5	350	167	174	174	20.8
14	DC12-70	12	70	M5	260	167	213	216	21.5
15	DC12-80	12	80	M5	260	167	213	216	23.2
16	DC12-90	12	90	M5	305	167	210	213	26.8
17	DC12-100	12	100	M5	330	173	217	220	30
18	DC12-120	12	120	M5	406	173	236	236	35
19	DC12-150	12	150	M5	486	171	243	243	43
20	DC12-180	12	180	M5	494	206	209	235	54
21	DC12-200	12	200	M5	523	240	219	223	60.5
22	DC12-250	12	250	M5	520	269	220	224	72.8
23	DC2-100	2	100	F10/M8	170	72	205	228	5.9
24	DC2-200	2	200	F10/M8	171	111	328	340	12
25	DC2-250	2	250	F10/M8	171	111	328	340	16
26	DC2-300	2	300	F10/M8	170	150	330	342	18.8
27	DC2-400	2	400	F10/M8	210	175	334	365	24.5
28	DC2-500	2	500	F10/M8	241	172	338	365	29.7
29	DC2-600	2	600	F10/M8	300	175	334	365	36.5
30	DC2-800	2	800	F10/M8	410	175	331	365	48
31	DC2-1000	2	1000	F10/M8	474	173	329	366	60
32	DC2-1200	2	1200	F10/M8	474	173	329	366	62.5
33	DC2-1500	2	1500	F10/M8	398	350	341	383	95
34	DC2-2000	2	2000	F10/M8	490	350	342	381	129
35	DC2-2500	2	2500	F10/M8	712	353	341	382	171
36	DC2-3000	2	3000	F10/M8	712	353	341	382	188