

GEL Battery Series

Lead Acid Battery

· Capacity range: 26AH to 3000AH

Rated voltage: 2V, 6V, 12V

• Designed floating charge life: 15-20 years

• Ultra-long discharge cycle

· Manufactured with high-porosity

· High gas recombination efficiency

 Special lead calcium alloy composition, which improves corrosion resistance of grids and increases the battery service life

PVC-SiO separators and world-leading 2 SiO gel technology

 High heat capacity, reducing risks of thermal runaway and dehydration, suitable for use in rigorous environments



No.	Model	Rated Voltage (V)	Rated Capacity (AH)		Battery Dimension (mm)				Weight (Kg)
						Width		Total Height	
1	DG6-100	6	100	M8	194	170	205	205	15.8
2	DG6-190	6	190	M8	243	187	253	276	31
3	DG12-18	12	18	L1/M5	181	77	167	167	5
4	DG12-24	12	24	L1/M5	175	166	125	125	7.5
5	DG12-28	12	28	L1/M5	175	166	125	125	8
6	DG12-28L	12	28	L2/M5	165	126	174	174	9
7	DG12-33	12	33	L3/M5	196	133	161	170	10.2
8	DG12-40	12	40	L4/M5	196	165	170	170	12.5
9	DG12-55	12	55	M5	230	137	210	215	17
10	DG12-60	12	60	M5	350	167	174	174	20
11	DG12-65	12	65	M6	350	167	174	174	21
12	DG12-70	12	70	M6	260	167	213	216	24
13	DG12-80	12	80	M6	305	167	210	213	27.5
14	DG12-90	12	90	M8	305	167	210	213	28.5
15	DG12-90H	12	90	M8	330	173	217	220	31
16	DG12-100	12	100	M8	330	173	217	220	32
17	DG12-110	12	110	M8	330	173	217	220	33.5
18	DG12-120	12	120	M8	406	173	236	236	36.5
19	DG12-134	12	134	M8	342	172	280	280	42.5
20	DG12-150	12	150	M8	486	171	243	243	44
21	DG12-160	12	160	M8	530	207	214	214	53
22	DG12-180	12	180	M8	494	206	209	209	55
23	DG12-200	12	200	M8	523	240	219	223	66
24	DG12-250	12	250	M8	520	269	220	224	75
25	DG12-50FT	12	50	M6	277	106	221	221	17
26	DG12-100FT	12	100	M8	506	110	224	239	31
27	DG12-150FT	12	150	M8	551	110	287	287	47
28	DG12-180FT	12	180	M8	546	125	317	323	57
29	DG2-100	2	100	F10/M8	170	72	205	228	6
30	DG2-200	2	200	F10/M8	171	111	328	340	14
31	DG2-250	2	250	F10/M8	171	111	328	340	16.5
32	DG2-300	2	300	F10/M8	170	150	330	342	19.5
33	DG2-400	2	400	F10/M8	210	175	334	365	26.5
34	DG2-500	2	500	F10/M8	241	172	338	365	31.5
35	DG2-600	2	600	F10/M8	300	175	334	365	38
36	DG2-800	2	800	F10/M8	410	175	331	365	53
37	DG2-1000	2	1000	F10/M8	474	173	329	366	62
38	DG2-1200	- <	1200	F10/M8	474	173	329	366	
39	DG2-1200	2	1500	F10/M8	398	350	341	383	64 97
40	DG2-2000	2	2000	F10/M8	490	350	342	381	130
41	DG2-2500	2	2500	F10/M8	712	353	341	382	172
41 42	DG2-2500 DG2-3000	2	3000	F10/M8	712	353	341	382	198
42	: 102-3000	.;4	3000	LTO\IAIQ	: 112	: 353	541	.; 38∠	198